

IM50 F18 LITHIUM



PRODUCT DESCRIPTION

- Cordless gas fine finish nailer for straight brads 18-gauge from 16 to 50mm

PRODUCT PROMISE

Premium gas driven fine finish nailer, with Lithium technology

FEATURES AND BENEFITS

- Quick charge lithium battery: Up to 10,000 shots per full charge
- Improved weight and balance allows any user to manoeuvre into tight spaces, fatigue free
- Easy use tool free depth adjustment for consistent excellent finishing
- Optimum line of sight and no-mar tip
- On / Off battery position for optimised capacity
- Reversible belt hook and easy jam clearance

APPROVALS



APPLICATIONS

- Skirting boards
- Cabinet work
- Furniture trim
- Glazing bead
- Exhibition & display work
- Shop fitting & remodelling
- Beading
- Panelling
- Secret nailing

SUBSTRATES



SAFETY



PRODUCT RANGE

Item Description ▲▼	First Packaging Unit (Smallest Selling Unit) (Level 0) ▲▼	Quantity ▲▼	Product Code ▲▼
Impulse fine finish nailer IM50 F18 Lithium EU	PLASTIC CASE	1	013332

CONSUMABLES



F18 ELECTROGALV 3µm BRADS
Indoors, Service Class 1

	▲▼ Fastener Length	▲▼ Fuel Cells	▲▼ Nail Head Type	▲▼ Quantity	▲▼ Eurocode
	16 mm	2	Full head	2000	395192*
	25 mm	2	Full head	2000	395193*
	32 mm	2	Full head	2000	395194*
	38 mm	2	Full head	2000	395195*
	50 mm	2	Full head	2000	395196*



F18 STAINLESS STEEL A2 BRADS
Outdoors, Service Class 3

	▲▼ Fastener Length	▲▼ Fuel Cells	▲▼ Nail Head Type	▲▼ Quantity	▲▼ Eurocode
	32 mm	2	Full head	2000	395465*
	38 mm	2	Full head	2000	395466*
	50 mm	2	Full head	2000	395467*

ACCESSORIES



Eurocode 018881
Battery charger for Impulse
lithium tools EU



Eurocode 018880
Li-ion Battery for IM360Ci /
PPN35Ci / IM350+ / IM65 /
IM65A / IM50



Eurocode 300341
Mini Fuel Cell Blister Pack
Yellow



Eurocode 013690
Impulse & Pulsa Cleaning Kit



Eurocode 115251
Impulse Cleaner 300ml



Eurocode 014979 
IM65 / IM65A / IM50 Lithium
Tool Carry Case



Eurocode 401482
Impulse Lubricating Oil



Eurocode 900507
In-car Charger Adaptor

TECHNICAL INFORMATION

Battery

Description ▲▼	Values ▲▼
Fixings Per Battery Charge	10000 shots
Battery Charge Time	90 Min.
Battery Type	Lithium

Tool

Description ▲▼	Values ▲▼
Weight According EPTA (Kg)	2,1 kg
Net Depth Dimension	307 mm
Net Length Dimension	288 mm
Net Width Dimension	90 mm
Power (Impact Force)	25 J
Magazine Capacity	100 fixings
Fuel Cell Capacity	1000 shots
Operating Temperature Range	+5°C...+49 °C
Fixings Per Hour	1000 fixings
Fixings Per Sec	2-3 fixings

Consumables

Description ▲▼	Values ▲▼
Fastener Length Range	16-50 mm

Safety

Description ▲▼	Values ▲▼
Peak Sound Pressure (En 12549) Lpcpeak	< 130 dB(C)
Sound Pressure Level (En 12549) Lpa,1S,1M UoM	dB(A) 88
Vibration (EN ISO 8662-11) hav	2,3 m/s²